



Kongeriget Danmark


Patent application No.: PA 2003 01761
 Date of filing: 28 November 2003
 Applicant: Coloplast A/S
 (Name and address) Høltedam 1
 DK-3050 Humlebæk
 Denmark

REC'D 03 JAN 2005	
WIPO	PCT

Title: En bandage

IPC: A 61 F 13/02; A 61 L 15/58

This is to certify that the attached documents are exact copies of the above mentioned patent application as originally filed.



Patent- og Varemærkestyrelsen
 Økonomi- og Erhvervsministeriet

PRIORITY DOCUMENT
 SUBMITTED OR TRANSMITTED IN
 COMPLIANCE WITH
 RULE 17.1(a) OR (b)

17 December 2004

Susanne Morsing

BEST AVAILABLE COPY

28 NOV. 2003

Modtaget

TITLE

An adhesive patch

BACKGROUND OF THE INVENTION**5 1. Field of the Invention**

The present invention relates to adhesive patches, in particular patches for covering, healing and treating a portion of the anatomical surface of a human being and a method for preparing such patches.

10 2. Description of the Related Art

Conventionally, dressings or patches for the treatment or prevention of wounds or pressure sores or even unbroken skin comprise a backing layer and an adhesive layer. The adhesive layer is often bevelled at the edge portions in order to have a smooth appearance, and avoid wrinkling and focusing of stresses in the dressing often causing slipping of the adhesive and unintended detachment of the dressing. The central portion of the dressing may be quite thick in order to provide a cushioning effect and/or an absorbent effect. However, a thick dressing may be less flexible and less capable of following the movements of the skin, as well as it appears very visible at the skin.

20

It is often desired to have a dressing or patch, which is very discreet or even "invisible". This may be the case when the patch is worn in the face or on other exposed areas. The patch may be used for covering scratches, wounds, acne, scars or discoloured skin and may have to purposes: To camouflage irregularities at the skin and/or to treat the skin site, e.g. a wound or acne. Different product for these purposes is known. These are usually in the form of adhesive patches or dots to be applied on the desired body part. Most of them are rather thick and thus rather unflexible and often quite visible. Some may contain medicaments for topical delivery.

25 30

US Patent No. 5,785,978 discloses an adhesive patch comprising active ingredients. The patch comprises an occlusive backing film and an adhesive

layer. The shape of the patch is adapted to the body part on which they are applied. The patch is occlusive and thus not breathable and does not comprise any absorbent elements and may thus give rise to unwanted humidity under the patch resulting in irritation of the skin and reduced wear time.

5

None of the known products address the problems associated with the problem of producing an adhesive patch being capable of blending into the skin in such a way that it may appear almost invisible.

- 10 It has now been found that the patch of the present invention fulfils the above-mentioned demands by providing an almost invisible patch with long wear time.

SUMMARY OF THE INVENTION

- 15 The invention relates to an adhesive patch for covering a portion of the anatomical surface of a human being, said patch being able to adhere to the skin, and/or a wound, said patch comprising a backing layer and a layer of a skin-friendly adhesive for adhering to the skin, said adhesive comprises hydrocolloid particles.

- 20 One object of the invention is to provide a non-occlusive adhesive patch, i.e. one that will enable moisture on the surface of the skin to evaporate through the patch so as to prevent the undesired accumulation of moisture, which, if occurred, could cause the patch to fall off or even facilitate the growth of bacteria beneath the patch.

25

Another object of the invention is to provide a lighter, more flexible and less obtrusive patch while still providing the excellent wear time and healing properties.

- 30 Yet another object of the invention is to provide an adhesive patch being ultra-thin or having ultra thin portions and capable of blending into the skin, rendering it extremely discreet for the user.

Detailed Description of the Present Invention

The invention relates to an adhesive patch for covering a portion of the anatomical surface of a living being, said patch being able to adhere to the skin, and/or a wound, said patch comprising a backing layer and a layer of a skin-friendly adhesive for adhering to the skin, said adhesive comprises hydrocolloid particles, wherein at least along the periphery of the patch the thickness of the adhesive layer is 20–300 μm and the vapour permeability of the patch is 200–2000 g/m^2 .

10 The adhering surface preferably comprises hydrocolloid particles, the thickness of the adhesive being in the range of 25–300 μm , such as 30–200 μm , such as 25–150 μm , such as 30–100 μm , and the vapour permeability of the dressing sheet being 200–6000 g/m^2 , such as 200–2000 g/m^2 , such as 200–1000 g/m^2 , such as 15 300–800 g/m^2 , such as 400–700 g/m^2 , such as 450–650 g/m^2 measures over 24 hours. It has been found that a dressing sheet with such thickness and vapour permeability provides a non-occlusive adhesive dressing sheet, i.e. one that enables moisture on, e.g., a skin surface to evaporate through the dressing sheet, so as to prevent undesired accumulation of moisture which could cause 20 the dressing sheet to loose its adhering contact to the skin or promote bacterial growth between the sheet and the skin. Moreover, the small thickness of the dressing sheet results in a discrete appearance once applied to the application site.

25 Though the term adhesive is used herein it is understood that the term may cover any substance having adherent properties, such as adhesives, silicone or rubbery substances, petrolatum or the like, and hydrocolloid adhesives. The adhesive may be a pressure sensitive adhesive of any suitable kind known per se.

30 The thickness of the adhesive layer of the patch of the present invention may be substantially constant over the surface or the patch may have a thicker portion at

the centre of the patch, surrounded by a thinner periphery, i.e. a bevelled edge. It has surprisingly been shown that a better performance for the patch is achieved by having a thin edge portion. The thin periphery of the patch decreases the risk of rolling-up of the edge portion. The rolling up of the edge portion may lead to reduced wear time and is undesired. Furthermore, the thin edge portion is less exposed to water coming from outside, and renders it possible to obtain an extreme water-block.

It is preferred that the thickness of the adhesive layer is 20-200 μm , more preferred 25-150 μm and most preferred 30-100 μm .

A thin layer of adhesive is desired, as this will reduce the overall thickness of the patch. The thinner the dressing or patch is, the more flexible and more capable of following the movements of the body it is and the more discrete it appears.

The dressing or patch is especially suitable for use in the face or other visible or exposed areas of the body and it is thus desired that the patch blends into the skin and appears almost invisible.

Due to the reduced thickness of the patch it is possible to produce patches for scratches, wounds and for reducing scarring. The patch may work like a second skin.

The surface area of the dressing sheet may e.g. be 5-25 cm^2 , such as 10-20 cm^2 , or smaller, such as less than 5 cm^2 , such as at most 4 cm^2 , such as at most 2 cm^2 , such as in the range of 1-2 cm^2 , or smaller, such as 0.08 – 1 cm^2 , such as 0.1 – 0.8 cm^2 , such as 0.12 – 5 cm^2 . For facial application, e.g. of a thin film patch, the surface area is usually less than 5 cm^2 .

The vapour permeability of the patch is preferably 300-800 g/m^2 , more preferred 400-700 g/m^2 , and most preferred 450-650 g/m^2 .

The patch may have an optimal balance between a limited absorption and an appropriate permeability. Together these properties provides a patch with excellent moisture handling qualities compare to common thin dressings which may have a thicker layer of adhesive and/or a non-absorbing adhesive.

5

In one embodiment of the invention the patch may have bevelled edges. The bevelling may provide a smoother transition between the patch and the skin, rendering the patch more invisible.

- 10 The outer periphery of the patch is preferably bevelled in analogy with the disclosure of US Patent No. 4,867,748 or US patent No. 5,133,821 in order to reduce the risk of "rolling-up" the edge of the patch reducing the wear-time. The edge is preferably bevelled so that the thickness adjacent to the edge does not exceed about 30% of the maximum thickness of the patch; more preferred not
- 15 exceeding 25% of the maximum thickness.

- The patch of the invention has surprisingly good water resistance, and bevelling of the edge may further enhance these properties. Preferably the edges are bevelled to a thickness of approximately 50 my. By the expression "water
- 20 resistance" is understood that after application of the patch to the body part, the patch is capable of resisting numerous times of exposures to water or humidity, such as bathing hand washing, swimming or perspiration.

- The excellent water resistance and the good moisture handling qualities render it
- 25 possible to achieve an extremely long wear time for the patch compared to commonly known products.

- The patch may be prepared by a one step process, where a high flexibility in production may be achieved, thin bevellings may be prepared, with adapted
- 30 centre thickness, and at the same time sufficient capacity to absorb exudates from a wound or blister.

The adhesive of the patch of the invention may be any suitable skin-friendly adhesive. The adhesive further comprises particles of hydrocolloids and/or super absorbing particles or fibres.

- 5 The skin-friendly adhesive may be any skin-friendly adhesive known per se for production of medical articles, which are to be adhered to human skin, preferably an adhesive comprising hydrocolloids or other moisture absorbing constituents for prolonging the time of use. The adhesive may suitably be of the type disclosed in US patent Nos. 4,231,369, 4,367,732, 4,867,748, and 5,714,225.
- 10 Especially preferred are the adhesives disclosed in US patent Nos. 4,367,732, and 5,714,225.

- 15 The patch of the invention may in one embodiment of the invention be in the form of a mono-phase adhesive, i.e. made from one adhesive component or in accordance with another embodiment of the invention be in the form of a two-zone adhesive, e.g. of the general type disclosed in US patent No. 5,714,225, i.e. a part of or all of the adhesive areas of the patch having maximum thickness being constituted by more than one type of adhesive.

- 20 The particle size of the hydrocolloid particles influence on the thickness of the adhesive layer, as it is difficult to prepare an adhesive layer being thinner than the size of the hydrocolloid particles.

- 25 The physical form of conventional hydrocolloids is relative coarse and irregular particles, typically about 60-100 μm and in the form of a dry powder. In order to obtain finer particles, the hydrocolloid may be milled and/or sifted.

- 30 Suitable hydrocolloids for the patch of the present invention include synthetic polymers prepared from single or multiple monomers, naturally occurring hydrophilic polymers or chemically modified naturally occurring hydrophilic polymers. The hydrocolloid polymers may be linear or cross linked. This include natural or chemically modified natural polymers like celluloses such as CMC.

chitosan, pectin, guar gum, starches or dextrines, collagenes and gelatine and synthetic polymers like polyacrylic acid, polyvinylealcohol/acetate, polyhydroxyalkyl acrylates and methacrylates, polyacrylamides, polystyrene sulfonates, polyvinyl pyrillidone, polyglycols, copolymers, grafts of such, copolymers or compositions of such.

In a preferred embodiment of the invention the hydrocolloid particles have a size being substantially less than 100 μm , more preferred less than 75 μm and most preferred less than 50 μm .

The adhesive layer may be in the form of a pattern, such as geometric pattern or a random pattern, or the adhesive layer may comprise larger interruptions in the form of areas with no adhesive, e.g. the central part of the patch.

It is preferred that the adhesive layer is uninterrupted. The uninterrupted layer provides several advantages, such a less wrinkling, better invisibility and better blending into the skin. Backing layer being uncoated with adhesive may be more non-transparent and thus more visible. Furthermore, the pattern may leave marks on the skin when the patch is removed.

The adhesive patch may be in a flat continuous layer from 20 g/m^2 up to 1000 g/m^2 .

The patch of the invention is suitable for covering cuts, grazes and abrasions, scars, wrinkles, discolouring of the skin or the like. The patch may be especially suitable for treatment of herpes, as the patch may be applied to the lip or lip region being discrete and without causing discomfort.

It is suitable that the backing layer is a substantially water-impervious film which protects the adhesive from being adversely affected when the wearer is bathing or in case of incidental wetting of the area and especially when the adhesive is water absorbing.

The backing layer may be any water impervious layer or film may be of any suitable material known per se for use in the preparation of wound dressings e.g. a foam, a non-woven layer or a polyurethane, polyethylene, polyester or
5 polyamide film. In accordance with the invention it has been found in practice that the use of a thinner backing layer or film than is normally used when preparing medical dressings, an improved stretchability and adaptability is obtained at the same time as the modulus is reduced.

10 The backing layer may preferably be an elastic, flexible and non-sticking film that protects the adhesive during storage as well as during use.

The water impervious, but vapour permeable layer or film is preferably a low-friction flexible polymer film reducing the risk of unwanted stress in the area of
15 application.

An especially suitable material for use as a water impervious film is a polyurethane film. A preferred low friction film material is disclosed in US patent
20 No. 5,643,187.

The backing layer may have a suitable thickness for the intended use. If the patch were desired for an "invisible" face patch, a rather thin film would be appropriate. It is preferred that the backing layer has a thickness of less than 30
25 μm .

25 A preferred thickness of this film may be below 20 microns, more preferred about 12-18 microns, e.g. about 15 microns, thus resulting in a significant decrease of the modulus, compared to a film that is normally used when preparing medical dressings. An improved stretchability and adaptability is obtained at the same
30 time as the modulus is reduced.

In accordance with a preferred embodiment the backing layer is a film showing a low surface friction. Furthermore, the surface may be opaque, with a reflection being near to the reflection of skin, thus enabling the patch to blend with the skin colour and reflection and be less visible.

5

The backing layer may be coloured in suitable colours, e.g. flesh-colour or it may carry ornaments. The backing layer may be transparent, opaque or non-transparent, depending on the intended use.

- 10 A patch of the invention may preferably be sterilised for avoiding the risk of causing infections when applied to skin areas having broken skin.

It is not critical whether or not the patch is sterilised, if the patch is applied to non-broken skin, e.g. on a face portion for camouflaging irregularities of the skin, such as scars.

15

Preventing and protecting against abrasion may also be considered as an aspect of the present invention.

- 20 The patch of the invention is optionally covered in part or fully by one or more release liners or cover films to be removed before or during application.

A protective cover or release liner may for instance be siliconized paper. It does not need to have the same contour as the patch, e.g. a number of patches may be attached to a larger sheet of protective cover. The protective cover is not present during the use of the patch of the invention and is therefore not an essential part of the invention.

25

- 30 Furthermore, the patch of the invention may comprise one or more "non touch" grip(s) known per se for applying the patch to the skin without touching the adhesive layer. Such a non-touch grip is not present after application of the patch. For larger patches it is suitable to have 2 or 3 or even 4 "non-touch" grips.

The patch of the invention may further comprise one or more cover layers. The cover layer may protect the patch during storage and help easy application of the patch. The cover layer is removed during or after application.

5

Preferably, in all embodiments of the present invention, the patch is provided in the form of a backing layer with an adhesive applied to one surface thereof. The adhering surface of the patch may comprise a pharmaceutically active substance. For example, emollients or e.g. retinoids for treating or preventing formation of psoriasis, eczema, callous, skin, corns or blisters. Examples of applicable pharmaceutical medicaments include a cytokine, such as a growth hormone or a polypeptide growth factor such as TGF, FGF, PDGF, EGF, IGF-1, IGF-2, colony stimulating factor, transforming growth factor, nerve stimulating growth factor and the like giving rise to the incorporation of such active substances in a form being apt to local application in a wound in which the medicament may exercise its effect on the wound, other medicaments such as bacteriostatic or bactericidal compounds, e.g. iodine, iodopovidone complexes, chloramine, chlorhexidine, silver salts such as sulphadizine, silver nitrate, silver acetate, silver lactate, silver sulphate, silver sodium thiosulphate or silver chloride, zinc or salts thereof metronidazol, sulpha drugs, and penicillins, tissue-healing enhancing agents, e.g. RGD tripeptides and the like, proteins, amino acids such as taurine, vitamins such as ascorbic acid, enzymes for cleansing of wounds, e.g. pepsin, trypsin and the like, proteinase inhibitors for use in e.g. surgical insertion of the dressing in cancer tissue and/or other therapeutic agents which optionally be used for topical application, pain relieving agents such as lidocaine or chinchocaine, emollients, retinoids or agents having a cooling effect.

10

15

20

25

30

Due to its discrete appearance and the easy applicability provided by the carrier system, the dressing of the invention may advantageously be used for facial application, such as for the treatment of herpes, acne and warts with medicaments known per se for such purposes being contained in the adhesive or being applied thereto. Suitable anti viral medicaments for the treatment of herpes

may for example comprise aciclovir or penciclovir. Azelain acid or isotretinoin may be used in a medicament for the treatment of acne. In respect of the treatment of warts, a mitotic inhibitor, such as podophyllotoxin, is applicable. Warts and/or callous skin may be treated by salicylic acid-based medicaments.

5

The above mentioned pharmaceutically active substances may be applied to the adhering surface of the dressing sheet after completion of the adhering coating, or they may be mixed into the adhesive prior to coating thereof onto the backing layer.

10

In one embodiment of the invention the medicament may be applied to the patch before application. The patch may comprise one or more cavities for accommodating a medicament. The cavities may be in the form of a dome shaped portion or an indentation.

15

The patch may comprise an absorbent pad. The absorbent pad may be any suitable absorbent material, such as gauze, alginates, hydrocolloids or super absorbers. In one embodiment of the invention the pad comprises an adhesive. The adhesive may be the same adhesive as on the patch or it may be a different adhesive, e.g. a more absorbent adhesive.

20

Claims

1. A patch for covering a portion of the anatomical surface of a living being, said patch being able to adhere to the skin, and/or a wound, said patch comprising a backing layer and a layer of a skin-friendly adhesive for adhering to the skin, said
5 adhesive comprises hydrocolloid particles, wherein at least along the periphery of the patch the thickness of the adhesive layer is 20-300 μm and the vapour permeability of the patch is 200-1000 g/m^2 .
2. A patch according to claim 1 wherein the thickness of the adhesive layer is 30-
10 200 μm .
3. A patch according to claim 1 or 2 wherein the vapour permeability of the patch is 300-800 g/m^2 .
- 15 4. A patch according to any of claims 1-3 wherein the patch has bevelled edges.
5. A patch according to any of claims 1-4 wherein the hydrocolloid particles have a size being substantially less than 100 μm .
- 20 6. A patch according to any of claims 1-5 wherein the hydrocolloid particles have a size being substantially less than 50 μm .
7. A patch according to any of claims 1-6 wherein the backing layer is a polyurethane film.
25
8. A patch according to any of claims 1-7 wherein the backing layer has a thickness of less than 30 μm .
9. A patch according to any of claims 1-8 wherein the adhesive layer is
30 uninterrupted.

13

10. A patch according to any of claims 1-9 wherein the patch comprises an absorbent pad.

5 11. A patch according to any of claims 1-10 wherein the patch comprises one or more cavities.

Abstract**An Adhesive patch**

- 5 A patch for covering a portion of the anatomical surface of a living being, said patch being able to adhere to the skin, and/or a wound, said patch comprising a backing layer and a layer of a skin-friendly adhesive for adhering to the skin, said adhesive comprises hydrocolloid particles, wherein at least along the periphery of the patch the thickness of the adhesive layer is 20–300 μm and the vapour
- 10 permeability of the patch is 200–1000 g/m^2 .

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.